

TSC

The Smarter Choice.

CELEBRATING 20 YEARS



ME240 SERIES – Industrial Thermal Transfer Bar Code Printer

SMALL FOOTPRINT DELIVERS YOUR EVERYDAY LABEL PRINTING NEEDS



KEY FEATURES

- 2-button 3-LED (basic model)/6-button LCD (advanced model) control panel
- Easily adjustable sensors
- Print head pressure adjustment knobs
- 450 meter ribbon capacity
- Die-cast print mechanism for custom applications
- Flexible firmware structure allows the printer to emulate popular printer languages
- Available in 203 dpi and 300 dpi resolutions
- Up to 4 GB Flash memory expansion using SD Flash memory
- Fast label throughput

APPLICATIONS

- **Warehousing/Distribution**
 - Labeling for
 - Packing
 - Shipping
 - Inventory Management
 - Shelf/Rack Labeling
- **Manufacturing**
 - Work In Process Labeling
 - Product Marking
 - Inventory Management
- **Compliance Labeling**
- **Healthcare**
 - Patient ID
 - Pharmacy Unit Dose
 - Specimen Labels
 - Wristband Printing
 - Admissions

ME240 SERIES – Industrial Thermal Transfer Bar Code Printer

PRINTER MODEL	ME240	ME340
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer & Direct Thermal	
Max. print speed	152 mm (6")/second	102 mm (4")/second
Max. print width	104 mm (4.09")	104 mm (4.09")
Max. print length	2,286 mm (90")	1,016 mm (40")
Enclosure	Die-cast based print mechanism/Metal cover with large clear media view window	
Physical dimension	286 mm (W) x 259 mm (H) x 434 mm (D) 11.26" (W) x 10.20" (H) x 17.09" (D)	
Weight	11 kg (24.25 lbs)	
Label roll capacity	203.2 mm (8") OD	
Ribbon	450 m long, max. OD 81.3 mm, 1" core (ink coated outside)	
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")	
Processor	32-bit RISC CPU	
Memory	<ul style="list-style-type: none"> • 4 MB Flash memory • 8 MB SDRAM • SD Flash memory card reader for Flash memory expansion, up to 4 GB 	
Interface	<ul style="list-style-type: none"> • RS-232 • USB 2.0 • Internal Ethernet, 10/100 Mbps (factory option) • USB host, for scanner or PC keyboard (factory option) • Centronics (factory option) • Bluetooth (user option) • External 802.11 b/g/n wireless (user option) 	
Power	Internal universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 2.0A, 47-63Hz • Output: DC 24V, 3.3A, 80W 	
LCD	<ul style="list-style-type: none"> • Basic model without LCD • Advanced model with Graphic type, 128 x 64 pixel, with back light 	
Operation switch, button	<ul style="list-style-type: none"> • 1 power switch, 2 buttons (Pause, Feed) - Basic model • 6 buttons (Menu, Pause, Feed, Up, Down, Select) - Advanced model 	
Sensors	<ul style="list-style-type: none"> • Gap transmissive sensor (position adjustable) • Black mark reflective sensor (position adjustable) • Ribbon end sensor • Head open sensor 	
Real time clock	Standard	
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font 	
Bar code	<ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11, Logmars • 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec 	
Font and barcode rotation	0, 90, 180, 270 degree	
Printer language	TSPL-EZ™	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	25.4 ~ 118 mm (1.0" ~ 4.6")	
Media thickness	0.06 ~ 0.28 mm (2.36 ~ 11 mil)	
Media core diameter	25.4 mm ~ 76.2 mm (1" ~ 3")	
Label length	5 ~ 2,286 mm (0.2" ~ 90")	5 ~ 1,016 mm (0.2" ~ 40")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing	
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, UL, CUL, TÜV/Safety, CCC	
Environmental concern	Comply with RoHS, WEEE	
Accessories	<ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord • Ribbon paper core • 3" media core adapter x 2 	
Limited warranty	<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first 	
Factory options	<ul style="list-style-type: none"> • Graphic type, 128 x 64 pixels LCD display • Internal Ethernet interface (10/100 Mbps) • USB host, for scanner or PC keyboard • Centronics parallel interface 	
Dealer options	<ul style="list-style-type: none"> • Peel-off module • Guillotine cutter (full cut) 	
User options	<ul style="list-style-type: none"> • Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard 	



- CORPORATE HEADQUARTERS**
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: printer_sales@tscprinters.com
- LI ZE PLANT**
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: printer_sales@tscprinters.com
- AMERICAS**
TSC Auto ID Technology America Inc. Corporate Office
 Tel: +1 909 525 9779
 E-mail: sales@tscprinters.com
- Orlando Office**
 Tel: +1 407 704 8918
 E-mail: sales@tscprinters.com
- CANADA**
TSC Auto ID Technology America Inc.
 Tel: +1 909 525 9779
 E-mail: sales@tscprinters.com
- MEXICO**
TSC Mexico Representative Office
 Tel: +52 (33) 3836 6682
 E-mail: sales@idc-componentes.com
- BRAZIL**
TSC Brazil Representative Office
 Tel: +55 (11) 9597 8098
 E-mail: paul_liao@tscprinters.com
- EMEA**
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 00
 E-mail: info@tsceu.com
- RUSSIA**
TSC Auto ID Technology EMEA GmbH
 Tel: +7 915 422 8889
 E-mail: victoria.grobushkina@tsceu.com
- MIDDLE EAST**
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: info@tscmea.com
- ASIA PACIFIC**
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: printer_sales@tscprinters.com
- CHINA**
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: sale@tscprinters.com.cn