



 G-6000

G-6000

The G-6000 industrial standard printer was developed to give you high speed performance and an extended printed area with its 6-inch printing width. The built-in LCD display, 2 MB flash memory, and PS2 interface for your PC keyboard provides the essentials for Plug-and-Play stand-alone operation. The perfectly designed metal case resists rough treatment, heat, and dust, and ensures continuous quality operation, even in the most demanding environments. Superior historical control enhances printing quality and is perfect for bar code and small alphanumeric printing. The G-6000 is simple to operate and allows the user to easily perform adjustments and maintenance.



Argox can.



ARGOX
Empower the Barcode

Provide a full range of products of outstanding quality?

Specifications	G-6000
Print Method	Direct Thermal & Thermal Transfer
Printing Resolution	203dpi (8 dots/mm)
Printing Speed	2 ~ 6 ips (51 ~ 150 mm/s)
Printing Length	1" ~ 30" (25mm ~ 762mm)
Printing Width	Max 6.0" (152mm)
Memory	2MB DRAM, 1MB Flash ROM
CPU Type	32 bit RISC microprocessor
Media Sensor	Reflective/See-through (Adjustable)
Display	Back-lit LCD, 2-line x 6, LED Indicator x 3
Operation Interface	Buttons x 3
Communication Interface	Centronics parallel RS-232 serial
Fonts	Int'l character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23"H (1.25mm ~ 6.0mm) All fonts are expandable up to 24 x 24 4 direction 0° ~ 270° rotation Soft fonts are downloadable
Barcodes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417, Data Matrix
Graphics	PCX bit map, GDI graphics
Software	Argox PPLA Language Windows Driver (Win 98/2000/NT/XP) Label editing software - ArgoBar Print Utility
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper and fabric label with face-in media run way Max width 6.3" (160mm) Min width 1" (25mm) Thickness 0.0025" ~ 0.01" (0.0635mm ~ 0.254mm) Max roll capacity 8" (203mm) OD Core size 1.5" ~ 3.0" (38 ~ 76 mm) ID
Ribbon	Wax, Wax/Resin, Resin with inside coating Ribbon width - 2", 4", 6" Ribbon roll - max OD 2.5" (63mm) Ribbon length - max 300M wax Core size - ID 1" core (25mm)
Dimensions	W310 x H260 x L445 mm, 3.2 lbs (14.5kgs)
Power Source	110 ~ 220 VAC ±10%, 50/60 Hz, internal Universal Power Supply
Agency Listing	CE, UL, CUL, FCC, CCC
Operational Items	40° F ~ 100° F (4° C ~ 38° C) ; 10 ~ 90% non condensing
Optional Items	Cutter, Dispenser kit, Real time clock card, ArgoNet print server, USB interface, 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese)

Specifications subject to change without notice