

T6000

HIGH-PERFORMANCE THERMAL PRINTER

SPEED VERSATILITY

RELIABILITY







The Powerful T6000 represents the next generation industrial, high-performance thermal barcode printer.

Setting new benchmarks for speed, print quality, validation and reliability, the T6000 is engineered with the singular mission of increasing true productivity and lowering compliance fees. Loaded with advanced features, validation technology, RFID capabilities and the most comprehensive emulation package available, the T6000 delivers supercharged performance for a wide array of applications.



SPEED

- Stellar quality print at lighting fast speed, clocking in at 14 ips
- Increased productivity at every shift as a direct result of the ARM Cortex-A9 controller, processing barcode data faster than ever before
- Ease-of-Use and an interactive screen reduces training and down time, helping your business focus on operational productivity



VERSATILITY

- Plug-n-Play in any operational environment, with the ability to be networked via the most comprehensive printer emulations in the industry
- Rugged design allows the T6000 to perform in even the most challenging environmental conditions
- Wide-ranging RFID support for On-Pitch, Short-Pitch and Standard Pitch to handle a variety of applications



RELIABILITY

- Exclusive validation solutions eliminate expensive compliance fees by producing 100% quality barcodes, 100% of the time
- Comprehensive WiFi security suite featuring the very latest protocols to block unauthorized access and ensure peace of mind
- Intelligent heat management system increases printhead life and improves barcode print quality while reducing operating costs

REAL WORLD BUSINESS APPLICATIONS THAT GIVE YOU THE EDGE ON YOUR COMPETITORS

- With industry-leading validation technologies like ODV that support the latest compliance labeling requirements your supply chain is now fortified with cutting-edge traceability applications that also eliminate costly compliance fines
- Easy integration in any legacy environment with full provisions for any Warehouse Management System helping you increase uptime and prevent loss of productivity
- Powers through the most rigorous shifts while handling multiple label applications- from 'Pick and Pack' support and cross-docking applications to labels for cases, pallets, packages, shipment slips, invoices, etc.

POSTSCRIPT/PDF FOR YOUR MOST COMPLEX LABELING NEEDS

- The T6000 is engineered to support all major ERP systems
- Plug-n-Play with native SAP drivers to expand your operational abilities
- Full range of fonts and symbols gives you the tools required to customize your labels to suit your unique application and environment

PRINTNET ENTERPRISE AUTO ID:

- Printronix Auto ID provides a unique remote printer management tool to monitor, configure and support printers from anywhere in the world
- Instant email and mobile phone alerts allow you to mitigate issues or designate events in real-time, maintaining continuous network health and peak performance
- Fully compatible with any Printronix Auto ID product

GENUINE PRINTRONIX SUPPLIES:

Our commitment to your particular application does not end at your printer. Instead, our promise of reliability continues throughout the life of your application and with every single printout. Genuine Printronix Supplies meet the stringent performance standards required by our printers and ensure optimum performance at every shift, every single day. With extensive manufacturing capabilities and multiple distribution points, our product experts can deliver custom solutions for a wide variety of applications.

SAY GOODBYE TO BAD BARCODES.
With compliance fines as high as
\$10,000, it is more critical than ever
to print clean, readable barcodes.
Online Data Validator (ODV) reads
every barcode as it's printed. And if
there is an error, the printer strikes
through the bad barcode and
reprints a new one.



T6000

SPECIFICATIONS

PRODUCT BENEFITS

- High performance ARM Cortex-A9
- Die-cast aluminum frame w/metal door
- Transfer and direct printing
- 4" and 6" model configurations
- Premium Asian and Andale font support
- * State-of-the-art WiFi connectivity
- Available in 203 DPI and 300 DPI
- 512MB RAM / 128MB Flash Memory
- 4-32 GB SD memory card capability
- **ENERGY STAR Certified**

PRINTER SPECIFICATIONS

14/12 IPS @ 203 DPI; 12/10 IPS @ 300 DPI Max Print Speed (4"/6") Print Method Transfer and Direct

Max. Print Width 4.1" (104mm) / 6.6" (168mm) 512MB RAM / 128MB Flash Printer Memory

MEDIA SPECIFICATIONS

Resolution

Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets Media Type Min. Media Width (4"/6") 1" (25.4mm)/2" (50.8mm)

203 DPI / 300 DPI

Max. Media Width 4.5" (114.3mm) / 6.8" (172.7mm)

0.25" / 1.0" (Continuous/Tear-Off) / 1.0" (Peel-Off) Min. Media Length

Up to 99" Max. Media Length

2.5 Mil (0.0025") to 10 Mil (0.010") Media Thickness Media Roll Core Diameter 1.5" (37.5mm) to 3.0" (76mm)

Max. Media Roll Diameter 8.0" (209mm) Media Sensing Gap, Mark

RIBBON SPECIFICATIONS

Ribbon Type Wax, Wax/Resin, Resin Coated side in, coated side out Coating Min. Ribbon Width (4"/6") 1" (25 4mm)/2" (50 8mm) Max. Ribbon Width (4"/6") 4.5" (114.3mm)/6.8" (172.7mm)

Max. Ribbon Length

PHYSICAL CHARACTERISTICS

Width (4"/6") 10.9" (276.9mm)/14.1" (358.1mm) Height (4"/6") 12.3" (312.4mm)/12.4" (314.9mm) 20.3" (515.6mm)/20.3" (515.6mm) Depth (4"/6") Printer Weight (4"/6") 33.6 lbs. (14.5Kg)/39 lbs. (17.4Kg) Shipping Weight (4"/6") 42.6 lbs. (18.6Kg)/48 lbs. (21.5Kg)

PRINTER LANGUAGE

PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL **IGP** Languages PJL, XML, and PTX-SETUP Job Control Languages

Optional Languages IPDS

TN5250

PDF Level 1.7, Postscript Level 3

COMMUNICATION AND CONNECTIVITY/INTERFACE

Standard Interface I/O Serial RS232, USB, and Ethernet 10/100Base T Optional Interface I/O Parallel, WiFi (802.11a/b/g/n), GPIO WFP 40/128bit, WPA Personal (PSK). WiFi Security Protocol

> WPA2 Personal (PSK) and Enterprise (AES CCMP) EAP-TLS, EAP-TTLs, PEAPv0/MS-CHAPv2, PEAPv1

EAP-MD5

MEDIA HANDLING MODES

Standard Continuous, Tear-Off Strip, Tear-Off Options Peel-Off, Cut, and Rewind











Contact your local Printronix Auto ID authorized reseller.





BARCODE VALIDATION

Online Data Validator (ODV) Validates, Grade, Report, and Overstrike bar codes Supports 1D Barcodes (Picket Fence)

Compatible with RFID encoding

RFID

UHF EPC Gen2 / ISO18000-6C

Multi-position RF antenna, Advanced Printer Encoder Firmware encodes and validates Gen2 compliant tags On-Pitch label to 0.625 in (depending on inlay) PGL, ZPL, STGL, MGL language support Counters track good / bad label encoding

OPERATING ENVIRONMENT

40 to 104°F (5 to 40 °C) Operating Temperature Operating Humidity 20 - 85% Non-Condensing Storage Temperature -40 to 140 °F (-40 to +60 °C) Storage Humidity 5 - 85% Non-Condensing

POWER REQUIREMENT

Line Input Auto Range 100 - 264 VAC (48 - 62 Hz)

REGULATORY COMPLIANCES

FCC, CE, CCC Emissions Safety cTUVus, CE, EAC, SABS, RCM, CCC, KCC, S-MARK, NOM Environmental RoHS, WEEE, Energy Star Radios (WiFi/RFID) FCC, CE, IC, and others based on market need

BAR CODE SYMBOLOGIES

1D Barcodes BC-412, Code 11, Code 39, Code 35, Code 93, Codabar, Code128 Subsets A/B/C. Industrial 2 of 5. Interleave

2 of 5, German I-2/5, EAN-8, EAN-13, UCC/EAN-128, UPC-A, UPC-E, UPCSHIP, UPS 11, MSI, Matrix 2 of 5, PLESSEY, POSTNET, 4-state PostBar, Australian 4-state, FIM, ITF14, TELEPEN, PLANET, USPS Intelligent Mail,

LOGMARS

PDF-417, MicroPDF-417, Maxicode, DataMatrix, QR Codes, Aztec, GS1 Databar (RSS-14)

FONT, GRAPHIC SUPPORT

Graphic Formats Font Technologies Standard Fonts

2D Barcodes

Asian Fonts (Optional SD card) Andale Fonts (Optional SD card) PDF/ PostScript Level 3

PCX, TIFF, BMP, PNG Intellifont, TrueType, Unicode OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate/Bold/Condensed

Simplified Chinese, Japanese, and Korean Simplified Chinese, Traditional Chinese, Korean, Japanese 35 Fonts

REMOTE MANAGEMENT SOFTWARE

PrintNet Enterprise Auto ID

Enterprise Grade Remote Management Solution

OPTIONS AND ACCESSORIES

- WiFi 802.11 a/b/g/n (US/EU/CAN)
- Parallel Port
- **GPIO**
- TN5250
- PDF/PostScript
- Online Data Validator (ODV)
- Rewind 4"/6"
- Heavy Duty Cutter 4"/6"
- Peel & Present 4"/6"
- **Premium Asian Font Cards**
- Andale Font Cards
- QCMC (SD Quick Change Memory Card)
- UHF RFID (US 902-928MHz, EU 866-868MHz)





printronixautoid.com

© 2016 Printronix Auto ID, Inc. All rights reserved. Printronix Auto ID and all product names, numbers and logos are trademarks or registered trademarks of Printronix, Inc. Product appearance and/or specifications are subject to change without notice. Windows® is a registered trademark of Microsoft Corporation™ in the United States and other countries. All other trademarks, product names and company names and logos herein, are the property of