



Operation System

CPU	1.4GHz, Qualcomm 8917 Quad core
Memory	2GB DDR RAM 16GB ROM
OS	Android 7.1 Enhanced security by preventing 3rd party data collection (without GMS).
Languages	Multi-language
Others	Input Chinese/ English, supports handwriting and soft keyboard.

Display

5.0 inch TFT-LCD HD (720 x 1280) color screen, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance.

Buttons

Side SCAN button x 2 (Left / Right), User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button.

Camera/Photos/Video

2MP front camera
8MP rear camera with LED flash and auto-focus function

Symbologies 2D Imager

1D/2D All major 1D and 2D codes

RFID

HF/NFC Frequency 13.56Mhz
Support: ISO14443A/B, ISO15693 standard,
Supports NFC

Device supported MDM

SOTI, 12Manage and MoboLink

Regulatory Approvals

CE, R&TTE, NCC, CCC, VCCI

Communication

USB	Micro USB
OTG	Yes, over Micro USB
POGO PIN	Charging via cradle and USB client
WLAN	802.11 a/b/g/n/ac
Bluetooth	Bluetooth 4.1
WWAN	EU 4G FDD-LTE(B1, B2, B3, B7, B8, B20, B28A, B28B) 3G UMTS/HSDPA/HSPA/HSPA+ (900, 1900,2100MHz) US 4G FDD-LTE B1,B2,B4,B7,B5,B20,B28A,B28B 3G UMTS/HSDPA/HSPA/HSPA+ (850,1900, 2100MHz) 2G GSM/EDGE/GPRS(850,1900) CN 4G FDD LTE B1,B3& TDD B38,39,40,41 3G UMTS/HSDPA/HSPA/HSPA+ (900,2100 MHz) CDMA EV-DO Rev.A (800MHz), Band 34, 39
Sensors	Proximity sensor, light sensor and G-sensor

Audio

Microphone, speaker and 3.5mm audio jack

Expansion Slot

Micro SD/TF x 1(maximum of 32 GB), Micro SIM x 2

Enclosure

Dimension 158 mm x 76.2 mm x 11.5 mm
Weight 210g

Environmental

Operating temperature	-10°C to +50°C
Storage temperature	-20°C to +70°C
Charging Temperature	0°C to 40°C
Relative Humidity	5% ~ 95% (non-condensing)
Drop Specification	1.5m to concrete
Sealing	IP67

Accessories

Single slot USB cradle

Indicator

LEDs, Vibrator

Power Source

Main battery	Rechargeable and Changeable (Non-swappable) 3.8 V, 3800mAh Polymer Li-ion battery built-in.
Operation time	10-12 hours (depending on the specific environment)
RTC battery	Real time clock battery

Warranty

1 Year Terminal and cradle / 3 months battery.



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

